



GRIP A936 XPRESS

HIGH-PERFORMANCE PRIMER FOR NON-ABSORBENT SUBFLOORS

Date: 01 December 2020

Fact Sheet No.: TDS02159

YOUR SMART ADVANTAGES

- High grip, contains quartz
- Fast drying
- Solvent-free and odourless

USES

Bostik GRIP A936 XPRESS is a water-based primer and adhesion promoter, which increases the adhesion between self-levelling compounds and substrates. The primer is coloured to identify coated areas.

Bostik GRIP A936 XPRESS can be used as a primer/bonding agent prior to the application of any of the Bostik Screedmaster range of smoothing compounds. It can be used on all internal, smooth, dense, and non-absorbent concrete surfaces, ceramic tiles, quarry tiles, terrazzo, rigid metal, asphalt and surface membranes. It can also be applied over hard, sound and watertight adhesive residues and well-adhered floor paint. Bostik GRIP A936 XPRESS is suitable for use with underfloor heating.

PRODUCT CHARACTERISTICS

Colour	White (dries translucent)
Form	Liquid
Specific Gravity	1.0 approx.
Composition	Water-based solution
Product Codes	30615707 7kg
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +10°C to +30°C and out of direct

sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+10°C to +25°C
Coverage	Approx. 70m ² (depending on application technique)
Drying Times	60 minutes to 2 hours (depending on ambient temperatures)
VOC emissions	Very low emissions EC1 Plus
Cleaning	Clean tools and equipment with water immediately after use

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik GRIP A936 XPRESS, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

All phases of the installation should comply with the latest editions of the following standards:

- BS 8201 Code of Practice for flooring of timber, timber products and wood based panel products.
- BS 8102 Code of Practice for protection of building against water from the ground.
- BS 8203 Code of Practice for installation of resilient floor coverings.
- BS 5325 Code of Practice for installation of textile floor coverings.

PREPARATION

Subfloor:

1. Ensure the subfloor is sound, clean, dry (<75% RH) and of adequate tensile and compressive strength, free from loose material, laitance, cracks, structural defects, grease, oil, dirt, dust, surface hardeners, additives and

other surface contamination.

2. Adhesive residues that are hard, sound and watertight should be mechanically cut back to a minimum. Remove soft and weak adhesive residues.
3. The subfloor should also have an effective structural damp-proof membrane and be suitably dry.
4. The subfloor should be tested in accordance with British Standards using a properly calibrated and insulated hygrometer.
5. A reading of 75% RH or less confirms that the subfloor is satisfactorily dry. Where this has not been attained, it is necessary to apply a Bostik Screedmaster surface membrane to suppress residual moisture. For further information, contact Technical Services.
6. If any areas of the subfloor are in need of localised repairs, use Bostik Screedmaster Rapid Repair Mortar.

Underfloor heating systems:

7. Underfloor heating systems must be switched off for at least 48 hours before installation. Wait 48 hours after installation before gradually turning up underfloor heating.

APPLICATION

8. Apply using a short hair roller (4 to 6mm), ensure that the primer is worked well into the surface and that a thin, even coat is obtained. Do not allow to puddle.
9. Apply primer at a rate of 0.1kg per m².
10. Allow to dry and become transparent (approx. 2 hours), then apply a self-levelling compound. Keep the area dust free and apply the self-levelling compound within 24 hours of applying Bostik GRIP A936 XPRESS.

Existing ceramic tiles:

11. Check that tiles are firmly bonded and secure. Re-adhere any loose tiles and allow to dry.
12. Sand the tiles and thoroughly wash and degrease. Rinse carefully and let them completely dry before applying the primer.

Existing crunchy vinyl tiles:

13. Tiles must be firmly bonded and secure.
14. Remove any surface contaminants including any residues of adhesive. Thoroughly wash the tiles and let them dry completely before applying the primer.
15. Apply as above, at a rate of 0.1kg per m².

DRYING CONDITIONS

16. Bostik GRIP A936 XPRESS will cure between 60 minutes to 2 hours after application, depending upon substrate, temperature and ventilation. Under cold conditions, the curing rate will be considerably slower.

CLEANING

17. Clean tools and equipment with water immediately after use.

PRECAUTIONS IN USE

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik GRIP A936 XPRESS, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com