

# GO! Plasterboard Primer

Plasterboard primer



## THINNING

8-12%



## COVERAGE

10-12m<sup>2</sup>/L



## TOOLS

roller, brush,  
or airless  
spray gun



## DRY TO TOUCH

½-1 hours



Water borne white acrylic plasterboard primer for internal use. It is suitable to be applied on plasterboards but also on walls made of cement, plaster, etc. Provides an exceptional adhesion, opacity and a uniform appearance of the topcoat contributing to its higher spreading rate. It is recoated with all waterborne emulsion wall paints.

- » **Fills and covers the surface imperfections**
- » **Contributes to the topcoat's opacity**
- » **Recoated with all waterborne emulsion wall paints**

## TECHNICAL DATA

<b>Specific Gravity</b> {ISO 2811} @ 25°C	1.63Kg/L (±0.02)
<b>Solids Content w/w</b> {ISO 3251-03}	67.5% (±3)
<b>Stormer Viscosity</b> {ASTM D 562-05} @ 25°C	110KU (±15)
<b>Application Viscosity</b> {ASTM D 562-05} @ 25°C	85KU (±15)
<b>Gloss 60°</b> {ISO 2813-99}	<3.0 units
<b>Gloss 85°</b> {ISO 2813-99}	<12.0 units
<b>pH</b>	8.5-9.5
<b>Whiteness Index</b> {ASTM E 313-98}	88.0 (±1.5)
<b>Yellowness Index</b> {ASTM E 313-98}	1.0 (±0.5)
<b>Coverage per coat*</b>	10-12m <sup>2</sup> /L
<b>Recommended Dry Film Thickness (1 coat)</b>	40µm (±5)

\* Depending on the application conditions and surface absorption.



## Primers A/g (W/B).

- EU VOC Limit Value: 30g/L
- Maximum content of VOC of the product in a ready to use condition: 29g/L

# GO! Plasterboard Primer

## Plasterboard primer



### SURFACE PREPARATION AND APPLICATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint etc. Wet sanding is recommended for the surface preparation.

- » **On new surfaces:** apply one coat of KRAFT GO! PLASTERBOARD PRIMER.
- » **On surfaces that need filling:** use KRAFT SPACHTEL or KRAFT PUTTY or the suitable repairing material of KRAFT.
- » Allow new plaster or concrete to surfaces to cure a minimum of 30 days prior to primer application.

### APPLICATION INSTRUCTIONS

- » Before you start painting, dilute the primer 8-12% by volume with tap water and stir well.
- » Appropriate application tools for this product are brush, roller and airless spray gun.
- » Apply one coat of KRAFT GO! PLASTERBOARD PRIMER for the best result. Then apply 2 coats of the proper topcoat.
- » Minimum recoat time is 3-4 hours.
- » The surface drying time is ½-1 hours at 25°C and 50% relative humidity (drying times are longer in wet/cold conditions).
- » Do not apply at temperatures below 5°C and above 35°C and above 65% relative humidity.

### AFTER USE INSTRUCTIONS

- » Close the bucket undiluted to maintain in good condition for future use. Store before and after use in a cool place and away from sunlight or frost conditions.
- » Clean the tools thoroughly with water and soap.

### PACKAGING

- » Available in white in 3L and 9L containers.

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Telephone:

**+30 210 7793777**

### STORAGE

- » Store the product at temperatures between 5°C to 35°C.

**DISCLAIMER:** The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.kraftpaints.gr](http://www.kraftpaints.gr), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarben.gr](http://www.druckfarben.gr) | [www.kraftpaints.gr](http://www.kraftpaints.gr)



Toll-free number

**800 111 7700** Monday - Friday, 8.00 am - 04.00 pm

Email: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)