



# Profi Interior

Ecological emulsion paint



THINNING  
8-12%



COVERAGE  
12-14m<sup>2</sup>/L



TOOLS  
brush, roller,  
airless  
spray-gun



DRY TO TOUCH  
1-2 hours



Ecologically certified emulsion paint. It is friendly to the user and the environment, as it is certified by the Hellenic Council for EU Ecolabel Awards and fulfills the criteria of the EU Ecolabel. It does not contain harmful chemicals and it is virtually odorless, making it ideal for inhabited interior areas. It covers effectively, providing at the same time durable high whiteness and thousand unique shades. Due to its low gloss, it covers adequately the wall's imperfections and gives a smooth matt finish. It easy to apply, with even leveling, it dries quickly and it is ideal for frequent painting and freshening up.

- » High coverage
- » Smooth matt finish
- » Easy application

## TECHNICAL DATA

<b>Specific Gravity*</b> {ISO 2811 @ 25°C}	1.39-1.59Kg/L
<b>Solids Content w/w*</b> {ISO 3251-03}	62% (±3)
<b>Stormer Viscosity*</b> {ASTM D 562-05 @ 25°C}	110KU (±15)
<b>Application Viscosity*</b> {ASTM D 562-05 @ 25°C}	85KU (±15)
<b>Gloss 60°*</b> {ISO 2813-99}	<4 units
<b>Gloss 85°*</b> {ISO 2813-99}	<12 units
<b>pH</b>	8.5-9.5
<b>Whiteness Index**</b> {ASTM E 313-98}	90 (±1.5)
<b>Yellowness Index**</b> {ASTM E 313-98}	0.5 (±0.5)
<b>Coverage per coat***</b>	12-14m <sup>2</sup> /L
<b>Recommended Dry Film Thickness (2 coats)</b>	70µm (±10)

\* Depending on the tinting base and the shade

\*\* Only for White

\*\*\* Depending on the shade the application conditions and surface absorption



Interior matt walls and ceilings A/a (W/B).

- VOC Limit Value: 30g/L
- Maximum content of VOC of the product in a ready to use condition: 9.9g/L



# Profi Interior

## Ecological emulsion paint



### SURFACE PREPARATION

To ensure good adhesion, the surface must be dry, clean and free of dust, grease, residues, blistered paint etc.

Wet sanding is recommended for surface preparation.

- » **On new surfaces:** before applying the topcoat, apply one coat of a water-based primer such as KRAFT ECO DUR AQUA or KRAFT DUR AQUA WHITE or KRAFT HAFT.
- » **On surfaces that need repairing:** use KRAFT SPACHTEL or KRAFT PUTTY or the suitable repairing material of KRAFT.
- » **On surfaces with stain problems:** use first the insulating undercoat KRAFT ECO STAIN BLOCKER AQUA.

### APPLICATION INSTRUCTIONS

- » Before you start painting, dilute the paint by adding 8-12% by volume tap water and stir well.
- » Appropriate application tools for this product are brush, roller and airless spray gun.
- » The product shall be tinted with KRAFT INSPIRED COLOR tinting system to thousands shades. To ensure product quality it is required to tint the corresponding base selected from the tinting system of KRAFT.
- » **Surface drying time:** 1-2 hours at 25°C and 50% relative humidity (drying times are longer in wet/cold conditions).
- » **Minimum recoat time:** 3-5 hours.
- » For shade and finish consistency, it is advisable to use containers of the same batch number. In case of different batch number it is recommended that they be mixed in a large container.
- » Apply two coats of KRAFT PROFI INTERIOR for the best result.
- » In case of low opacity dark shades or with the appropriate labeling on the KRAFT INSPIRED COLLECTION color fan-deck it is recommended to apply KRAFT ECO STAIN BLOCKER AQUA tinted in the same colour family.
- » Avoid patching after finishing the painting. The difference of the substrate absorbance and application method might cause colour or gloss deviations. If it is necessary to repair apply the paint to the whole surface.
- » Do not apply at temperatures below 5°C and above 35°C and above 65% relative humidity.

### AFTER USE INSTRUCTIONS

- » Recover unused paint for reuse
- » Reuse of paint can effectively minimize the product's life cycle environmental impact.
- » Clean the tools thoroughly with water and soap.
- » Close the bucket to maintain in good condition for future use. Store before and after opening in a cool place and away from sunlight or frost conditions.

### PACKAGING

- » Available in White in 0.750L, 3L, 9L, 15L. Bases P,D, in containers of 1L, 3L & 9L.

### HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Read label before use. For further information please refer to the Material Safety Data Sheet.

Poison Centre Telephone:

**+30 210 7793777**

### STORAGE

- » Store the product before and after opening at temperatures between 5°C to 35°C.

**DISCLAIMER:** The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.kraftpaints.gr](http://www.kraftpaints.gr), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

### DRUCKFARBEN HELLAS S.A.

ASPROPYRGOS 19 300 ATTICA - GREECE | TEL.: +30 210 55 19 500 - FAX: +30 210 55 19 501  
[www.druckfarben.gr](http://www.druckfarben.gr) | [www.kraftpaints.gr](http://www.kraftpaints.gr)



Toll-free number

**800 111 7700** Monday - Friday, 8.00 am - 04.00 pm

Email: [paints.orders@druckfarben.gr](mailto:paints.orders@druckfarben.gr)