
Product data sheet

Status: 31.08.2023 | 21:18

Item no. 37814





Designation	Connecting profile for dry lining 12,5 mm PB
Description	PVC render stop with 6-mm shadow joint. For creating plastered single edges at plastered junctions, e.g. sliding ceiling and wall connections, for 12.5-mm plasterboard panels.
Product area	Internal construction
Product category	Design profiles
Plaster thickness	2,0 mm
Material	Hard PVC
GK/Plate	ab 12,5 mm
Product length	305,0 cm
Productcolor	10, white
Treatment	All profiles must also be fastened with clips.
Packaging Unit	50 STB / 80 KAR
shadow gap	6 mm

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general. Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!

PROTEKTORWERK Florenz Maisch GmbH & Co. KG

Postfach 1420, D-76554 Gaggenau Viktoriastr. 58, D-76571 Gaggenau Tel. +49 7225 977 - 0 Fax +49 7225 9 77 - 111 info@protektor.com www.protektor.com

