

PRODUCT DATA SHEET



Frameseal bead with protecting lip, mesh

6 mm

Item no. 37906



Status: 03.02.2025 | 11:02



Designation	Frameseal bead with protecting lip, mesh 6 mm
Description	The self-adhesive PROTEKTOR plaster sealing strip made of PVC with sewn-on alkali-resistant glass fibre fabric, protective lip and tear-off adhesive flap for foil covering is suitable for producing visually and technically perfect connections of windows, doors and other components to plaster and ETIC systems. With perforated plastering leg and sewn-on fabric for high-strength plaster binding. The foam tape is self-adhesive and closed-cell. Profile width 6 mm for ETIC systems and base plasters from 6 mm.
Product area	Thermal insulation
Product category	Soffit profiles
Plaster thickness	6 mm
Material	Rigid PVC with soft PVC and glass fibre mesh
Product length	260 cm
Product width	6 mm
Air and component temperature	+5° bis +40°C
Grammage	160 g/m ²
Mesh size	4 x 4 mm
Productcolor	10, white
Appearance	Self-adhesive, closed-cell foam tape.
Underground	Bonding areas must be even, dry (note possible condensation), free of frost, dust, grease, solid and load-bearing. An adhesive test indicates whether the substrate is suitable for bonding or whether special measures (e.g. cleaning) are required.
Treatment	For underground with lightness value greater than 7.
Packaging Unit	50 PCS / 13 BOX
Storage	Store profiles dry, frost-free, horizontally and flat in the box. Do not store or transport profiles which are twisted or bent. Protect cartons and/or profiles from excessive heat and direct sunlight. To remove the profiles, open the carton over its entire length.
Impermeability to driving rain	bis 1050 Pa
Annotation	One-sided tissue protrusion of 10 cm at the end of the bead.
product line	BasicLine

PRODUCT DATA SHEET

Frameseal bead with protecting lip, mesh

6 mm

Item no. 37906



Test report	Tested air, wind and driving rain tightness, tested movement absorption. The latest test reports are available for download at www.protektor.de .
Leaflet	* Leaflet * Fiche technique Formation de détails avec des profilés et des bandes d'étanchéité de joints pour l'enduit extérieur et l'ETICS, éditeur Verband für Dämmsysteme, Putz und Mörtel e.V. (VDPM). * Guideline for connections to windows and shutters in plaster, thermal insulation composite system and dry construction, published by the Baden-Württemberg Association of Plasterers for Interiors and Facades (SAF).
connection joint	Protective lip

This product data sheet corresponds to the current state of development of our products and loses its validity upon publication of a new edition. Make sure you are using the latest edition of this information. Warranty and liability are based on delivery according to our general Terms and conditions. Please observe the application assembly and storage guidelines.

All statements without guarantee. Reserve technical changes. Product illustrations may differ from the delivery product. Tender specifications, installation instructions and performance declarations (if required by law) can be found on our homepage. Please respect the environment for a proper disposal!